




NTN BEARING CORP.



20 mm x 52 mm x 15 mm NACHI NJ304EG cylindrical roller bearings

Bearing No. NJ304EG

NJ304EG Bearing 2D drawings and 3D CAD models

Size	20x52x15 mm
Bore Diameter	20 mm
Outer Diameter	52 mm
Width	15 mm
d	20 mm
Fw	27,5 mm
D	52 mm
B	15 mm
C	15 mm
r min.	1,1 mm
r1 min.	0,6 mm
Weight	0,15 Kg
Basic dynamic load rating (C)	31,5 kN
Basic static load rating (C0)	26,9 kN
(Grease) Lubrication Speed	12000 r/min
Enclosure	Open
Configuration	Single Row
Bore Type	Cylindrical Bore
Bore Size	20 mm
Outside Diameter	52 mm
Width	15 mm
Inside Ring Outside Diameter	27.5 mm
Fillet Radius/Chamfer	1.1 mm
r1	0.6 mm



NTN BEARING CORP.

Dynamic Load Rating	31,500 N
Static Load Rating	26,900 N
Limiting Speed - Grease	12,000 rpm
Limiting Speed - Oil	15,000 rpm
Radial Clearance	0.020 to 0.045 mm
db (min)	25 mm
db (max)	27 mm
dc (min)	30 mm
dd (min)	33 mm
Da (max)	45 mm
ra (max)	1 mm
ra1 (max)	0.6 mm